



NOMINAL LOADS	
GAS:	78.4 kW 400,000B.Th.U
ELECTRICITY 400V:	0 kW
ELECTRICITY 230V:	8 kW
DUCTING SIZE:	Ø250
FAN:	CNA 400 4000 m ³ /h
COLOR SPECIFICATIONS	
FRIER-SIDE (RAL-NO):	
CUST.-SIDE TOP(PRINT):	
CUST.-SIDE BTM (" "):	
SPECIALS	
Filtration system	
Halogens	
Separate return pipes	
Mirror glass doors	

Florigo Counterrange

THIS IS A CONCEPT-DRAWING – NOT TO SCALE –
 Unless expressly stated this drawing shall not be binding as to detail.

UPDATED 31-08-05

Waste oil dump tap
Mobile scrap box
Safety cut-out on all pans

CODERING	
1	2
OMSCHRIJVING	
WUZ.	DAT.

POS. / AANT.	BENAMING	MAT.	OPMERKING
SCHAAL:	DATUM: 03-06-05	AMPROL.	GET. J. van den End
5 Units Florigo Counterrange Electronic Ignition			
 FLORIGO PRIMO SOLUTIONS			FLORIGO UK LIMITED HENLEY-IN-ARDEN (UK) TEL. 01564 795545 FAX. 01564 795095
TEKENING NR.:			0514898-W2
WUZ.			

